

**Intended Use**

Allows miscellaneous devices (exits, emergency units, etc.) to become part of the OnePass system to be field installed by contractor. Also a plug-in connection for industrial fixtures that can be prewired by fixture manufacturer or field installed by contractor.

**OD**  
OnePass® Drop Cable



**Example:** OD 277 12/2G 15

**ORDERING INFORMATION**

For shortest lead times, configure products using **bolded options**.

Series	Voltage	Conductors <sup>1</sup>	Length <sup>4</sup>	Options	Finish <sup>3</sup>
<b>OD</b>	<b>120</b> 120V	<b>12/2G</b> Two 12AWG conductors plus one 12AWG ground	<b>01</b> 1 ft <b>20</b> 20 ft	<b>2N</b> Two circuit, two neutral <sup>2</sup>	RD Red
	<b>208</b> 208V	<b>12/3G</b> Three 12AWG conductors plus one 12AWG ground	<b>05</b> 5 ft <b>25</b> 25 ft		BK Black
	<b>277</b> 277V	<b>12/4G</b> Four 12AWG conductors plus one 12AWG ground	<b>10</b> 10 ft <b>30</b> 30 ft		WH White
	<b>240</b> 240V				BE Beige
	<b>347</b> 347V				
	<b>480</b> 480V				

**ADDITIONAL INFORMATION**

For additional product information, visit [www.relocwiring.com](http://www.relocwiring.com).

**Notes**

1. Conductors available in 12AWG only. 12AWG will plug into 10AWG product.
2. 2N available in 277V and 120V; 12/4G conductors only.
3. Colored cable available. Contact factory for other finishes.
4. Standard lengths listed. Consult factory for custom lengths.

**Intended Use**

Splits a branch circuit into two directions. Male/female component that can be used anywhere in the OnePass system.

**OSS**  
OnePass® Splitter Splice



**Example:** OSS 277 12/4G

**ORDERING INFORMATION**

For shortest lead times, configure products using **bolded options**.

Series	Voltage	Conductors <sup>1</sup>
<b>OSS</b>	<b>120</b> 120V	<b>12/4G</b> Four 12AWG conductors plus one 12AWG ground
	<b>208</b> 208V	
	<b>240</b> 240V	
	<b>277</b> 277V	
	<b>347</b> 347V	
	<b>480</b> 480V	

**ADDITIONAL INFORMATION**

For additional product information, visit [www.relocwiring.com](http://www.relocwiring.com).

**Notes**

1. Conductors available in 12/4G only. 12AWG will plug into 10AWG product.