

Intended Use

Located above the primary switch location to introduce local switching to the Quick-Flex system. Provides local switched power for fixtures and the ability to carry on-switched power to the next location through the use of a Quick-Flex Extender (QE).

System Features

1LEVEL/N includes a neutral wire that is required for single-level dimming devices.

QSD
Quick-Flex® Switch Drop



Example: QSD277 2LEVEL09

ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.

Series/Voltage		Conductors/Length ²		Options
Series	Voltage	Conductors	Length ²	
QSD	120 120V	1LEVEL Two 12 AWG conductors plus 12AWG ground	01 1 ft	HCF Meets healthcare facility requirements ¹
	277 277V	2LEVEL Four 12 AWG conductors plus 12AWG ground	09 9 ft	
	347 347V	1LEVEL/N Two 12 AWG conductors plus 12AWG ground and 12 AWG neutral	07 7 ft 13 13 ft 15 15 ft	

ADDITIONAL INFORMATION

For additional product information, visit www.relocwiring.com.

Notes

- 1 HCF is available with 2LEVEL and 1LEVEL/N conductors only.
- 2 Standard lengths listed. Consult factory for custom lengths.

Intended Use

Male/female cable that provides additional length anywhere within the Quick-Flex system.

QE
Quick-Flex® Extender



Example: QE277 12/3G15

ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.

Series/Voltage		Conductors/Length ¹		Options
Series	Voltage	Conductors	Length ¹	
QE	120 120V	12/2G Two 12 AWG conductors plus one 12AWG ground	05 5 ft	HCF Meets healthcare facility requirements
	277 277V	12/3G Three 12 AWG conductors plus one 12 AWG ground	09 9 ft	
	347 347V		11 11 ft 15 15 ft 21 21 ft 25 25 ft	

ADDITIONAL INFORMATION

For additional product information, visit www.relocwiring.com.

Notes

- 1 Standard lengths listed. Consult factory for custom lengths.

