

Intended Use

Used to split branch circuit into two directions in commercial or power applications.

SS

Splitter Splice



ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.

Example: SS 277 F U

Series	Voltage	Conductors	Factory keying	Options
SS	120 120V	F Five	U	CSA Meets Canadian standards ¹ IGW Isolated ground wire ²
	208 208V			
	240 240V			
	277 277V			
	347 347V			
	480 480V			

ADDITIONAL INFORMATION

For additional product information, visit www.relocwiring.com.

Notes

- 1 CSA option required for Canada.
- 2 IGW available with 120V only.

Intended Use

Introduces local switching to the 820 system. Located above primary switch location; provides local switched power and unswitched power to be used as needed.

ST

Switching Tee



ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.

Example: ST 277 D1 P U 08

Series	Voltage	Conductors/Switching function	Drop type	Factory keying	Length ⁴	Options
ST	120 120V	Conductors	P Protected	U	01 1 ft 06 6 ft 08 8 ft 09 9 ft 15 15 ft	N One neutral wire provided in drop ¹ CSA Meets Canadian standards ² HCF Meets healthcare facility requirements ³
	277 277V	1 One-level				
	347 347V	2 Two-level				

ADDITIONAL INFORMATION

For additional product information, visit www.relocwiring.com.

Notes

- 1 Neutral available with D conductor only.
- 2 CSA option required for Canada.
- 3 HCF available with E2 conductor only.
- 4 Standard lengths listed. Consult factory for custom lengths.