



# SURFACE MOUNT DOWNLIGHTS

## DIMMER COMPATIBILITY

FOR USE WITH:  
JSF AND JSFSQ

Type: \_\_\_\_\_

Catalog No.: \_\_\_\_\_

Project: \_\_\_\_\_

Notes: \_\_\_\_\_

### DEDICATED 120V FIXTURES

#### Incandescent and Magnetic Low Voltage - Forward Phase Dimming

Dimmable with the use of most forward phase dimmers • Dimming range of 100% down to 10% or lower with a minimum load of one fixture and a maximum load of 50% of the dimmer rated load; both dimming range and maximum rated load may vary depending on dimmer model.

#### Juno Qualified Dimmers include:

- |   |   |
|---|---|
| <p><b>Acuity Brands Model Numbers:</b></p> <ul style="list-style-type: none"> <li>• SensorSwitch™ WPD-WH</li> </ul> | <p><b>Lutron® Model Numbers:</b></p> <ul style="list-style-type: none"> <li>• Lutron® Radio RA2® RRD-10ND</li> <li>• Lutron® Radio RA2® RRD-PRO</li> <li>• Maestro® WIRELESS MRF2S-6ND</li> <li>• Caséta® PD-6WCL Series</li> </ul> |
|---|---|

#### Electronic Low Voltage - Reverse Phase Dimming

Dimmable with the use of most electronic low voltage dimmers • Electronic low voltage dimmers require a neutral wire in the wall box  
 • Dimming range of 100% down to 10% or lower with a minimum load of one fixture and a maximum load of 75% of the dimmer rated load; both dimming range and maximum rated load may vary depending on dimmer model.

#### Juno Qualified Dimmers include:

- Lutron® Model Numbers:**
- Diva® DVELV-300P
  - Maestro® MAELV\* Series
  - Maestro® MRF2S-6ELV\* Series
  - Caséta® PD-5NE Series

### UNIVERSAL VOLTAGE FIXTURES

#### Universal Voltage (120-277V) Housings - 0-10V Dimming Control

For use with many standard 0-10V dimming controls including Synergy ISD BC 120/277 • Dimming range of 100% down to 10% or lower with a minimum load of one fixture.

Consult technical services for additional information regarding other dimmer model qualification.