



MONOLINE®

Line Voltage 3 or 5 Light Kit
with SP1 1MLU Fixtures

MLKD1

Project: _____

Fixture Type: _____

Location: _____

Contact/Phone: _____

PRODUCT DESCRIPTION

Line voltage bendable track kit. The 4FT kit contains one 4' MLFT MonoLine track section with MLE End Caps, two MLSSR 5IN Standard Stem Supports, one MLP1 5IN Standard Stem Power Feed, three adjustable SP1 1MLU fixtures, and three 50W GU10 lamps. The 8FT kit contains two 4' MLFT MonoLine track sections with MLE End Caps, two MLSSR 5IN Standard Stem Supports, one MLS10 Conductive Connecting Support for Rigid Ceilings, one MLP1 5IN Standard Stem Power Feed, five adjustable SP1 1MLU fixtures, and five 50W GU10 lamps. Power feed cannot be extended. Standard offset is 5" from mounting surface to bottom of track. MonoLine may be bent to a minimum radius of 18".

PRODUCT SPECIFICATIONS

Electrical: 12 gauge solid copper conductors • Rated at 20 amps at 120 volts • Aluminum track used as system ground
• Fixtures rated at maximum 50W, GU10 lamp.

Hardware Finish: Satin Nickel (STN).

Glass Finish: Frost (FRTG).

Agency Approval

UL Listed for use in U.S. and Canada.

ORDERING INFORMATION

Series	Lengths	Finish	Accent Finish
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
MLKD1	4FT 4 FT Nominal Length 8FT 8 FT Nominal Length	STN Satin Nickel	FRTG Frost Glass

Ordering Example: MLKD1 4FT STN FRTG

LINE VOLTAGE 3 LIGHT KIT

