

Catalog Number
Notes
Type

FEATURES & SPECIFICATIONS

INTENDED USE — The industry's next generation in linear direct fluorescent products. This new compact, low-profile design offers our customers unique product features which improve the overall installation process and appearance while reducing labor cost, making it the most versatile solution for commercial, retail, manufacturing, warehouse, and cove and display applications.

CONSTRUCTION — Compact designed channel and cover are formed from code-gauge cold-rolled steel. Locking lamp holder tracks bolsters strength of the overall strip construction while creating improved lamp stability. Design includes T5 socket, features rotating collar and enclosed contacts. Improved easy "snap n' lock" end plates allow for quick attachment. Patented-pending "three-point" row connector locks channel together for straighter and faster rows mounting; included as standard.

Designed to accommodate T5HO lamp. Channel offers the gripper back feature which strengthens the overall construction. Patent-pending fastener-less channel cover offers a secure fit design allowing for quick attachment and easy access without pinching wires.

Finish: High-gloss, baked white enamel finish (white standard). Five-stage iron-phosphate pretreatment ensures superior paint adhesion and rust resistance.

ELECTRICAL — Thermally protected, resetting, Class P, HPF, non-PCB, UL listed. Suitable for damp locations. AWN, TFN or THHN wire used throughout, rated for required temperatures.

INSTALLATION — Patented-pending "three-point" row connector locks channels together for straighter and faster rows mounting; included as standard. Ideal for surface-mount or suspended.

LISTINGS — UL Listed, CUL Listed or CSA Certified to Canadian Standards. Listed for 25° C ambient temperature.

WARRANTY — Guaranteed for one year against mechanical defects in manufacture.

Note: Specifications subject to change without notice.



Low-Profile T5 Striplight


ZR



Linear Lamps
2 Lamps

Specifications

Length:	46 (116.8) or 92 (233.7)
Width:	2-1/8 (5.4)
Depth:	1-1/2 (3.8)
Weight:	7.1 lbs (3.2 kg)



All dimensions are inches (centimeters) unless otherwise noted.

ORDERING INFORMATION

For shortest lead times, configure products using **standard options (shown in bold)**.

Example: ZR 2 54T5HO MVOLT GEB10PS

Series	Number of lamps	Lamp type	Configuration	Paint finish	Reflector type	Voltage	
ZR Compact T5 For tandem double-length unit, add prefix T. ¹ Example: TZR	2 Not included	54T5HO 54W T5 HO (46")	(blank) No reflector	(blank) White	(blank) Solid	MVOLT¹	GEB10PS Electronic ballast, ≤10% THD, program start

Notes
1 MVOLT (120-277V), 50-60HZ.

MOUNTING DATA

For unit or row installation.

Unit installation — Minimum of two hangers required.

Row installation — One hanger per channel plus one per row required.

Review local codes when installing any product, as the minimum of 1 hanger per fixture may not satisfy your local building code.

