

Catalog Number
Notes
Type

FEATURES & SPECIFICATIONS

INTENDED USE

Small, attractive, round, outdoor remote core light. Ideal for use outside doorways to meet exit discharge requirements of the Life Safety Code. To be powered by 6- or 12-volt battery equipment as part of an emergency lighting system providing light for the path of egress.

CONSTRUCTION

Copper-free cast-aluminum face plate with stainless steel hardware. Standard with satin bronze finish. Weather-tight cable connector with 5', 12-gauge, 2-wire, low-voltage cable.


INSTALLATION

Installs with counter sunk 3/16" diameter screws (not provided).

Lamp: Variety of MR16 lamp wattages and voltages available.

Note: Specifications subject to change without notice.

Actual performance may differ as a result of end-user environment and application.



Unit Accessories

ELA CL

Core Light

ORDERING INFORMATION Lead times will vary depending on options selected. Consult with your sales representative. **Example: ELA CL H1006**

ELA		CL	
Series	Housing color	Fixture	Lamp type
ELA	(blank) Bronze	CL Round outdoor step light	H1006 10W/6V MR16 lamp H2006 20W/6V MR16 lamp H1012 10W/12V MR16 lamp H2012 20W/12V MR16 lamp

ELA CL Core Light

DIMENSIONS

All dimensions are inches (centimeters).

Shipping weight: 1 lb (0.45 kg)

