

TWR LED

Wall Luminaire

Familiar Design. New Technology.

Cast in a traditional dayform, the TWR LED luminaire offers a popular, classic appearance. Its advanced LEDs deliver an expected service life of more than 20 years and eliminate frequent lamp and ballast replacements associated with traditional technologies.

Key Features:

- Energy savings of up to 86% vs. comparable metal halide luminaires; saves up to \$214 per luminaire, per year over 400W metal halide
- 20+ years expected service life (with lumen maintenance of L90/100,000 hours)
- Prismatic glass lens protects the LEDs and provides even light distribution
- Traditional design allows for a seamless upgrade from HID, eliminating the need to repaint

TWR LED			
Model	Input Watts	Lumens	Metal Halide Replacement
TWR1 LED 1 50K	33W	3484	250W
TWR1 LED 2 50K	40W	4189	320W
TWR1 LED 3 50K	49W	5138	350W
TWR2 LED 1 50K	68W	7909	400W



Quick Facts:

- Replaces 250-400W MH
- Lumen packages from 3400 - 7900 lumens
- Input watts from 33-68W
- 5000K CCT and 4000K CCT available for TWR1; TWR2, 5000K CCT only

TWR LED Wall Luminaire

Ordering Information

EXAMPLE: TWR1 LED 2 50K MVOLT

TWR1 LED

Series	Performance Package	Color Temperature	Voltage	Controls	Finish
TWR1 LED	1 3480 lumens 2 4180 lumens 3 5130 lumens	40K 4000 K ¹ 50K 5000 K ¹	MVOLT ²	PE ³ MVOLT Photo Control	DDB Dark bronze

NOTES

- 1 Correlated color temperature (CCT) shown is nominal per ANSI C78, 377-2008.
- 2 MVOLT driver operates on any line voltage from 120-277V (50/60 Hz).
- 3 Photo control not available with 4000 K.

Ordering Information

EXAMPLE: TWR2 LED 1 50K MVOLT DDB

TWR2 LED

Series	Performance Package	Color Temperature	Voltage	Finish
TWR2 LED	1 7900 lumens	50K 5000 K ¹	MVOLT ²	DDB Dark bronze

NOTES

- 1 Correlated color temperature (CCT) shown is nominal per ANSI C78, 377-2008.
- 2 MVOLT driver operates on any line voltage from 120-277V (50/60 Hz).



TWR1 LED



TWR2 LED

Visit www.lithonia.com for more information