

FEATURES & SPECIFICATIONS

INTENDED USE

For use with frame-in LP6, LP6F and housings LI6 and LI6F.

CONSTRUCTION

Aluminum white polyester powder coat painted.

One piece reflector.

White integral flange as standard.

Engineering grade thermoplastic injection molded baffle in black or white.

Adjustable socket plate allows lamp to align perpendicular to the floor.

Accommodates ceiling pitch ranging from 2/12 to 12/12.

INSTALLATION

Socket to trim interface.

Rough-ins with clips retain trims.

LISTINGS

UL Listed to US and Canadian safety standards.

Damp location listed.

Patent # 5,452,193.

WARRANTY

1-year limited warranty. Complete warranty terms located at

www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Actual performance may differ as a result of end-user environment and application.

Note: Specifications subject to change without notice.

Catalog Number
Notes
Type

6" Full Reflector Trim

6SB1

SLOPED BAFFLE

Narrow Flange



Specifications


Height: 7-1/4 (18.4)

Lamp opening: 6 (15.2)

Diameter: 8-1/4 (21.0)

Trim height when used with
Non-IC incandescent rough-ins.

All dimensions are inches (centimeters) unless otherwise indicated.



ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

Example: 6SB1

6SB1		
Series	Finish	
6SB1	(blank)	Black baffle
	W	White baffle
	MW	Matte white

Housing Compatibility: Housing and trim ordered separately.			
Application	Source	Maximum wattage	Housing
IC	Incandescent	100 PAR38	LI6
		75 PAR30	
		65 BR40	
		65 BR30	
	Fluorescent	32TRT	LI6F
Non-IC	Incandescent	150 PAR38	LP6
		75 PAR30	
		120 BR40	
		65 BR30	
		100 A19	
	Fluorescent	32TRT	LP6F

6SB1 6" Sloped Baffle Full Reflector Trim

For BR and PAR reflector lamps, see lamp manufacturer's published raw lamp data for photometrics.