



Catalog Number	
Notes	
Туре	

# Contractor Select<sup>™</sup> **OFM LED** Canopy

The OFM LED canopy luminaire is a versatile and energy efficient solution for replacing 150W HID luminaires. Delivering up to 4,200 lumens using a modest 47 input watts, OFM LED provides a great, cost effective solution with an efficacy of 89 lumens per watt.

## FEATURES:

- Replaces up to 150W HID lamps, saves 80% energy
- Cost effective and energy efficient, Payback within two years
- Expected service life over 10 years no maintenance costs and hassles





Catalog Number	UPC	Description	Replaces Up To	Lumens	Wattage	сст	Voltage	Finish	Pallet qty.
OFM LED P1 50K MVOLT DDB HP17 M4	190887667011	CANOPY LUMINAIRE	150W HID	4,200	47W	5000K	120-277V	DARK BRONZE	96

More configurations are available. Click here or visit www.acuitybrands.com and search for OFM LED.





# Specifications

### INTENDED USE:

47 watt LED canopy light delivers 4,200 lumens for an energy-efficient replacement of 150W MH canopy/ceiling lights. Traditional style maintains current building aesthetics. The OFM LED provides years of maintenance-free general illumination for outdoor applications. Ideal for entrances, parking areas, covered walkways and loading docks.

### **CONSTRUCTION:**

Rugged cast-aluminum, corrosion-resistant housing with bronze polyester powder paint for lasting durability. Castings are sealed with a one-piece gasket to inhibit the entrance of external contaminants. Rated for outdoor installations, -40°C minimum ambient. Acrylic lens is designed for uniform light distribution. OFM LED is IP65 rated.

#### ELECTRICAL:

OFM LED delivers 4,200 lumens. Includes an MVOLT (120-277V) driver. LEDs maintain 72% of light output at 100,000 hours of service life (L84/100,000 hours).

#### INSTALLATION:

Mounts to a recessed junction box or surface mount with three conduit entry points Can be pendant mounted with  $\frac{3}{4}$  NPT pendant stem provided by others.

#### LISTINGS:

UL Listed to U.S. and Canadian safety standards for wet locations. Tested in accordance with  $\mathsf{IESNA}\,\mathsf{LM}\text{-}79$  and  $\mathsf{LM}\text{-}80$  standards.

DesignLights Consortium<sup>®</sup> (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at <u>www.designlights.org/QPL</u> to confirm which versions are qualified.


#### WARRANTY:

5-year limited warranty. Complete warranty terms located at: www.acuitybrands.com/CustomerResources/Terms\_and\_conditions.aspx

**Note**: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

# **Dimensions**

Width: 10"(25.4 cm) Height: 4"(10.16 cm) Depth: 10"(25.4 cm) Weight: 4.25lbs (1.93kg)



All dimensions are inches (centimeters) unless otherwise indicated.