

Catalog Number
Notes
Type

FEATURES & SPECIFICATIONS

INTENDED USE — Provides general illumination in residential and light commercial applications. Ideal for use in workshops, utility rooms and garages.

ATTRIBUTES — Slim, compact design available in 1- or 2- lamp configurations. Quality, postpainted steel construction.

MNS5 fixture ship standard with low-power factor magnetic ballast (120 volt, 60Hz).

MNS5 fixtures ship with 3000K linear fluorescent lamps. MNS8 fixtures are not available lamped.

MNS8 fixtures ship with normal power factor residential ballast (120 volt, 60 Hz) ensures no flickering and quiet operation. For use with non-dimmable switches only.

LISTINGS — CUL listed to US and Canadian safety standards and suitable for damp locations.

WARRANTY — 1-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at:

www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application.

Specifications subject to change without notice.

Fluorescent Mini-Strip T5 or T8 Striplight



ORDERING INFORMATION

Item	Catalog number	UPC	Description	# of lamps	Length	Width	Height	Wattage	Lamp type	Lamp include	Pallet Quantity	Standard Carton Quantity
*138RLM	MNS5 1 28 LP M6	745973907382	T5 mini-strip	1	46-3/4" (118.7)	1-1/2" (3.8)	2-1/8" (5.4)	28	T5	Y	240	1
*204RUF	MNS8 1 17 120 RE	745977729348	T8 mini-strip	1	24-3/8" (61.9)	1-5/8" (4.1)	2-3/4" (7)	17	T8	N	448	1
*204RUG	MNS8 1 25 120 RE	745977729386	T8 mini-strip	1	36-3/8" (92.4)	1-5/8" (4.1)	2-3/4" (7)	25	T8	N	192	1
*204RUH	MNS8 1 32 120 RE M6	745977729430	T8 mini-strip	1	48-3/8" (122.9)	1-5/8" (4.1)	2-3/4" (7)	32	T8	N	168	1

MNS5 and MNS8 Mounting Hole Dimensions

