

MARK Fin

A series of infinite possibilities



light as art

Lighting can be purely functional. It can be functional and aesthetic. Or it can be purely aesthetic.

Fin is light as art. Its role is not merely to illuminate a room but rather to spark the imagination. Its clean, simple, geometric form complements a wide range of environments and architectural designs and gives it timeless appeal.

A decorative accent fixture, Fin is versatile as well

as ornamental. It can be mounted horizontally or vertically and is available in a choice of clear sides with frosted edges or frosted sides with frosted edges. Lengths range from 2 to 8 feet, and the depth below the fixture door can be 2, 3 or 4 inches.

Use Fin to make a statement, to create interesting patterns of light, or to accentuate and enhance other design elements. You will discover the possibilities truly are infinite.



Specification Data

Housing: Housing and internal components fabricated from 20-gauge, cold-rolled steel.

Finish: Matte white.

Reflector: Precision-formed steel; white.

Shielding: Nominal 1 1/2"-thick acrylic fin.

Lamps: (1) T5 or T5HO lamp (provided by others).

Ballast: Thermally protected Class P energy-saving electronic ballast.

Mounting: Recessed in sheetrock ceiling; rod-mounted to structure. Consult factory for other ceiling types.

Certification: UL Listed, IBEW (Local 3) Union-made in the USA.

Photo: © Albert Vecerka/Esto

Example: FIN 2.2T5HO EBPR 120 CF

| Series | Length | Fin Depth Below Face of Door | Number of Lamps/Lamp type ¹ | Ballast | Voltage | Finish | Options |
|---------|--------|------------------------------|----------------------------------------|-------------------------------------|------------------|---------------------------------|-----------------------------|
| FIN Fin | 2 2' | 2 2" | Number of lamps 1 | EBPR Program rapid start (standard) | 120 | CF Clear sides, frosted edges | EMPK Emergency battery pack |
| | 3 3' | 3 3" | | T5 Instant start | 277 | FF Frosted sides, frosted edges | |
| | 4 4' | 4 4" | | T5HO Dimming (specify) | 347 ² | | |
| | 5 5' | | | T5S Lutron Hi-Lume® dimming | | | |
| | 6 6' | | | T5HOS Lutron Eco-10® dimming | | | |
| | 8 8' | | | EDES Lutron Eco System® | | | |

Notes 1. Consult factory for other lamps and for LED options. 2. Consult factory for lamp and ballast compatibility.