

# MARK® ARCHITECTURAL LIGHTING



## The Focus 58 Wall Series

A slender, low-profile luminaire with clean, crisp lines, Focus 58 Wall is a big performer, providing efficiencies as high as 98%. Featuring a 2-inch profile, it is just 3 3/4 inches deep and complies with ADA requirements.

It is available in 4- and 8-foot lengths and utilizes T5, T5HO or T8 lamps. Focus 58 Wall is the perfect complement to the Focus 58 pendant.

Type:

Project:

Catalog Number:

DO NOT TYPE HERE. Autopopulated field.

## Specification Features

### Housing

Nominal 4' and 8' housings fabricated from heavy-gauge extruded aluminum alloy.

### Ends and Connectors

Die-cast aluminum. Ends are quarter-round.

### Finish

Matte white.

### Reflector

Die-formed, prepainted-white steel.

### Shielding

Clear linear-ribbed acrylic lens.

### Lamps

(1) T5, T5HO or T8. Lamps provided by others.

### Ballast

Thermally protected Class P energy-saving electronic ballast.


### Mounting

Wall mounted.

### Certification

UL Listed, IBEW (Local 3) Union-made in the USA.

## Technical Drawings



## Ordering

Example: FSW 4 1T8 EBPR 120 IND

Series	Length	No. of lamps/Lamp type	Ballast	Voltage	Designation	Options
FSW Focus 58 Wall	4 Nominal 4' 8 Nominal 8'	Number of lamps 1 Lamp type T5 T5HO T8	EBPR Program rapid start (standard) EBIS Instant start EDB Dimming (specify) EDHL Lutron Hi-Lume® dimming EDE10 Lutron Eco-10® dimming EDES Lutron Eco System®	120 277 347 <sup>1</sup>	IND Individual BOR Beginning of row INT Intermediate EOR End of row	EMPK Emergency battery pack

### Notes

1 Consult factory for lamp and ballast compatibility.