

MARK[®] ARCHITECTURAL LIGHTING



The **Perimeter Plus** Series

With up to 40 feet of seamless reflector, Perimeter Plus is perfect for corridors and other long spaces. The white or semi-diffuse silver reflector can be field trimmed at job sites to accommodate any run length.

Standard 9-inch staggering of T5, T5HO or T8 lamps eliminates socket shadows and provides perimeter lighting for less than 8 watts per linear foot. Molded 90-degree inside and outside corners allow easy installation, and telescoping housing and lamp trays are standard.

Type:

Project:

Catalog Number:

DO NOT TYPE HERE. Autopopulated field.

Specification Features

Housing

Die-formed, 20-gauge, cold-rolled steel.

Ceiling and Wall Trim

Precision-extruded aluminum.

Finish

Matte white.

Reflector

Opaque white or silver metallic reflector in standard lengths up to 40 feet. Reflector can be field-trimmed with scissors or utility knife at job site to accommodate any run length.

Shielding

Unshielded. Open parabolic, silver or white reflector options available.

Lamps

Standard 9" stagger, (1) or (2) T5, T5HO or T8. Lamps provided by others.

Ballast

Thermally protected Class P energy-saving electronic ballast.

Mounting

Recessed perimeter wall wash in 8', 6', 4', 3' and 2' sections. Telescoping housing and lamp sections provided in all runs and patterns.


Corners

90-degree inside or outside molded corners.

Certification

cULus Listed, IBEW (Local 3) Union-made in the USA.

Technical Drawings



Ordering

Example: PPL 16FT WH 2T5S EBPR 120

Series	Length ¹	Color	Corner configurations	No. of lamps/Lamp type ²	Ballast	Voltage	Options
PPL Perimeter Plus	__ft. Provide wall-to-wall dimensions	SL Silver WH White	90IC 90° inside molded corner 90OC 90° outside molded corner	Number of lamps 1 2	Lamp type ² T5S T5HOS T8S	EBPR 120 EBIS 277 EDB 347 ³ EDHL EDE10 EDES	Program rapid start (standard) Instant start Dimming (specify) Lutron Hi-Lume [®] dimming Lutron Eco-10 [®] dimming Lutron Eco System [®]
							EMPK Emergency battery pack CP Chicago plenum

Notes

- 1 Provide field dimensions when placing order. For patterns, clearly indicate inside or outside corners. Upon request, factory will prepare installation drawings for approval.
- 2 Consult factory for other lamps.
- 3 Consult factory for lamp and ballast compatibility.