

MARK[®] ARCHITECTURAL LIGHTING



The Procyon Series

The sleek, shallow profile and refined curve of Procyon are accentuated by contoured die-cast aluminum end caps. The Procyon pendant is available with a choice of either perforated side panels with acrylic overlay or a solid body that provides all-indirect illumination.

Section lengths are 4 or 8 feet, and Procyon accommodates T5 or T5HO lamps. A wall-mount version is also available.

Type:

Project:

Catalog Number:

DO NOT TYPE HERE. Autopopulated field.

Specification Features

Housing

Nominal 4' and 8' housings fabricated from 18-gauge, cold-rolled steel.

Ends and Connectors

Die-cast aluminum.

Finish

Matte white.

Reflector

Die-formed semi-specular aluminum.

Shielding

PR1: perforated side panels with soft-white acrylic overlay. PR2: solid housing.

Lamps

PR1: (2 or 3) T5 or T5HO. PR2: (1, 2 or 3) T5 or T5HO. Lamps provided by others.

Ballast

Thermally protected Class P energy-saving electronic ballast.


Mounting

Pendant mounted with stainless steel cable. Vinyl power feed. 15' length provided as standard; gripper fitting allows quick length adjustment at job site. Units can be continuously rowed.

Certification

UL Listed, IBEW (Local 3) Union-made in the USA.

Technical Drawings



*Perforated area (Procyon 1 only; Procyon 2 is entirely indirect.)

Ordering

Example: PR1 4 CG 2T5HO EBPR 120 IND

Series	Length	Mounting	No. of lamps/Lamp type	Ballast	Voltage	Designation	Options
PR1 Procyon (perforated)	4 Nominal 4' 8 Nominal 8'	CG Cable and gripper	Number of lamps 1 ¹ Lamp type T5	EBPR Program rapid start (standard)	120 277	IND Individual	EMPK Emergency battery pack (small case only)
PR2 Procyon (solid)		CGPF Cable, gripper and power feed	2 3 Lamp type T5HO	EBIS Instant start	347 ²	BOR Beginning of row	
				EDB Dimming (specify)		INT Intermediate	
				EDHL Lutron Hi-Lume [®] dimming		EOR End of row	
				EDE10 Lutron Eco-10 [®] dimming			
				EDES Lutron Eco System [®]			

Notes

- 1 One-lamp option available only with PR2.
- 2 Consult factory for lamp and ballast compatibility.