

MARK[®] ARCHITECTURAL LIGHTING



The **Stick** Series

Stick's compact design, a nominal 3 inches wide by 3 inches deep, allows it to blend well in any environment. Units are available in 4- and 8-foot lengths and can be installed individually or in continuous rows.

Stick is offered with soft-white acrylic shielding below, providing a downlight glow that reduces contrast with the ceiling. A solid bottom is also available.

Type:

Project:

Catalog Number:

DO NOT TYPE HERE. Autopopulated field.

Specification Features

Housing

Nominal 4' and 8' housings fabricated from extruded aluminum.

Finish

Matte white.

Reflector

Die-formed aluminum; white.

Shielding

(STC - downlight) Soft-white acrylic.

Lamps

(1 or 2) T5 or T5HO. Lamps provided by others.

Ballast

Thermally protected Class P energy-saving electronic ballast.


Mounting

Pendant mounted with single stainless steel cable. White vinyl power cord. 15' length provided as standard; gripper fitting allows quick length adjustment at job site. Can be mounted in continuous rows.

Certification

UL Listed, IBEW (Local 3) Union-made in the USA.

Technical Drawings



Ordering

Example: STC 4 CG 1T5 EBIS 120 IND

Series	Length	Mounting	No. of lamps/Lamp type	Ballast	Voltage	Designation	Options
STC	4 Nominal 4'	CG Cable and gripper	Number of lamps	EBPR Program rapid start (standard)	120	IND Individual	EMPK Emergency battery pack
	8 Nominal 8'		1 T5	EBIS Instant start	277	BOR Beginning of row	
STS		CGPF Cable, gripper and power feed	2 T5HO	EDB Dimming (specify)	347 ¹	INT Intermediate	
				EDHL Lutron Hi-Lume [®] dimming		EOR End of row	
				EDE10 Lutron Eco-10 [®] dimming			
				EDES Lutron Eco System [®]			

Notes

1 Consult factory for lamp and ballast compatibility.